

Flexam EM 8/2 0+04 dark green AS FG



Article code 529106

General information	
Product group	Synthetic belts
Market segment	Agriculture, Paper, General handling, Distribution centres
Main features	Foodgrade
Belt support	Slider bed, Rollers, Flat

Belt construction			
Fabric tension layer	polyester	stable	2-ply
Topside	Flexam PVC	smooth	dark green
Bottomside	fabric	low friction	

Characteristics	
Foodgrade (FG)	yes
Antistatic (AS)	yes
High conductive (HC)	no
Flame retardant (FR)	no
ATEX approval	no

Technical belt data			
Hardness topside	according to DIN 53505	80A	shore
Force at 1% elongation	according to ISO 21181	8.0	N/mm 44.80 lbs./in.
Belt thickness	internal AB method KV.002	1.90	mm 0.075 in.
Weight	internal AB method KV.004	2.20	kg/m ² 0.451 lbs./ft. ²
Thickness top cover		0.40	mm 0.016 in.
Temperature range		-15 to 80	°C 5 to 176 °F
Temperature range short		-15 to 100	°C 5 to 212 °F
Min. pulley diameter flexing (A)		25.0	mm 0.984 in.
Min. pulley diameter back flexing (B)		50.0	mm 1.969 in.
Standard belt width		2000	mm 78.74 in.
Maximum belt width		3000	mm 118.11 in.

Endless instructions

Hot splicing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperatures and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

The diameters are valid for hot vulcanised splice and at the indicated belt force. Depending on the splice and working conditions (e.g. temperature), different pulley diameters may be possible or necessary. When fasteners are used the minimum diameters are increased by approx. 50%.

Consult our specialists for available profiles and accessories.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.